

AGENEWTECH

H1502UP

Smart Module Specification_V1.0



Our aim is to provide customers with timely and comprehensive service. For any assistance, please contact our company headquarters:

Wuxi Sunning Smart Devices Co.,Ltd.

No.52, Zone C, Huigu Pioneer Park, Huishan Economic Development Zone, Wuxi

Postal Code: 214174

PhoneNum: +86 0510 8235 0372 MailBox: Asupport@agenewtech.com

Introduction

AGENEW OFFERS THE DOCUMENT AS A SERVICE TO ITS CUSTOMERS. CUSTOMERS MUST DESIGN THEIR PRODUCTS ACCORDING TO THE SPECIFICATIONS AND PARAMETERS PROVIDED IN THE DOCUMENTS. AGENEW SHALL NOT BE LIABLE FOR ANY DAMAGE CAUSED BY FAILURE TO COMPLY WITH RELEVANT OPERATION OR DESIGN SPECIFICATIONS. AGENEW HAS THE RIGHT TO UPDATE THE DOCUMENT BEFORE IT IS ANNOUNCED.

Disclaimers

AGENEW MAKES EFFORT TO ENSURE THE INTEGRITY, ACCURACY, TIMELINESS OR UTILITY OF THE FUNCTIONS UNDER DEVELOPMENT, BUT DOES NOT EXCLUDE THE POSSIBILITY OF ERRORS OR OMISSIONS OF THE ABOVE FUNCTIONS. UNLESS OTHERWISE SPECIFIED VALID AGREEMENTS, AGENEW MAKES NO IMPLIED OR EXPRESS GUARANTEE FOR THE USE OF FUNCTIONS UNDER DEVELOPMENT. TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAWS, AGENEW SHALL NOT BE LIABLE FOR ANY LOSS OR DAMAGE SUFFERED DUE TO THE USE OF THE FUNCTIONS UNDER DEVELOPMENT, WHETHER SUCH LOSS OR DAMAGE IS FORESEEABLE OR NOT.

Copyright

THE INFORMATION CONTAINED HERE IS PROPRIETARY TECHNICAL INFORMATION OF WUXI SUNNING SMART DEVICES CO.,LTD. ANY COPIES AND REPRINTS THIS DOCUMENT WITHOUT THE PERMISSION OF AGENEW WILL BEAR LEGAL RESPONSIBILITY.

Copyright © Wuxi Sunning Smart Devices Co.,Ltd. 2021. All rights reserved.

About the Document


History

Version	Data	Author	Description
-	2024-02-21	Wang Chang	Initial
1.0	2024-02-22	Wang Chang	Controlled Copy

H1502UP

Multi-network Smart LTE module

Supports Wi-Fi & BT



H1502UP is a multi-network Smart LTE Cat 4 module based on MediaTek's Qcta-core ARM Cortex-A53 processor launched by Sunning Smart, equipped with Android 13 operating system. Its powerful performance, neon engine processing, 2D/3D graphics acceleration processing capabilities, fully meet the needs of customers for high-speed and multimedia functions in industrial and consumer applications.

H1502UP supports full coverage of all network systems, WI-FI 802.11a/b/g/n/ac, and BT5.0 near-field wireless communication. In addition, the H1502UP also has audio and video input and output interfaces and rich GPIO interfaces. It also supports a variety of audio and video codecs. The home screen supports HD+ 1280*800 at most. At the same time, H1502UP supports GPS+Glonass+BeiDou+Galileo positioning systems, making its positioning function fast and accurate.

H1502UP is a patch module with a total of 274 pins, including 146 LCC pins and 128 LGA pins. The size is only 40.5mm × 40.5mm × 2.8mm, which can be embedded in various M2M product applications through pads, making it widely used in smart cash registers, smart POS, tax control machines, security monitoring, vehicle equipment, and high-end information Collection equipment, smart robots, smart homes, smart hardware, industrial smart handheld devices, drones, high-end police or law enforcement equipment, smart intercom devices, smart wearables, vending machines, logistics cabinets and other equipment are used in different industries.



Main Advantages

- ✓ Comprehensive coverage of multi-network standard
- ✓ Support Wi-Fi 802.11a/b/g/n/ac and BT5.0 short-range wireless communication
- ✓ Support GPS/Glonass/BeiDou/Galileo and other standard satellite positioning
- ✓ Support multiple audio and video codecs
- ✓ The main screen supports up to FHD+ 1920×1200
- ✓ Support 1080P@60fps video recording and playback
- ✓ Possess audio and video input and output interfaces and rich GPIO interfaces



Qcta-core ARM Cortex-A53
64-bit processor



IEEE 802.11
a/b/g/n/ac



Support Android 13



GPS+Glonass+BeiDou+Galileo



Powerful multimedia



BT5.0

LTE Cat4	H1502UP
Region/Operator	China/Europe/Asia/South America
Operating System	Android 13
Memory	32GB eMMC + 4GB LPDDR4X/16GB eMMC + 2GB LPDDR4X/8GB eMMC + 1GB LPDDR3
Module size (mm)	40.5× 40.5× 2.8
Packaging	LCC + LGA
Temperature Range	
Operation Temperature	Normal operating temperature: -20 °C ~ + 80°C Storage temperature range: -40 °C ~ + 90 °C
Frequency Band Information	
LTE-FDD	B1/B3/B5/B7/B8/B20
LTE-TDD	B34/B38/B39/B40/B41B
WCDMA	B1/B2/B5/B8
GSM/EDGE	B2/B3/B5/B8
WLAN	2.4/5GHz, 802.11 a/b/g/n/ac
Bluetooth	BT5.0
GNSS	GPS+Glonass+BeiDou+Galileo
Authentication	
Operator Certification	Undetermined
Compulsory Certification	Undetermined
Other Certifications	Undetermined
Data Rate	
LTE-FDD (Mbps)	150Mbps (DL)/50Mbps (UL)
LTE-TDD (Mbps)	150Mbps (DL)/50Mbps (UL)
DC-HSPA+ (Mbps)	42Mbps (DL)/11.2Mbps (UL)
WCDMA (Kbps)	384Kbps (DL)/384Kbps (UL)
EDGE (Kbps)	296Kbps (DL)/236.8Kbps (UL)
GPRS (Kbps)	107Kbps (DL)/85.6Kbps (UL)
Outstanding characteristics	
Six-Mode	LTE: Release 12 UMTS: Release 9
Bandwidth (MHz)	1.4/3/5/10/15/20
Rx-Diversity	●
DL supports MIMO 2 × 2	●
SIM Card Detection	●
Dual SIM Dual Standby	●
USB Firmware Upgrade	●
OTA Firmware Upgrade	●

Remarks: 1. *: In progress

2. ●: Supports

LTE Cat4	H1502UP
Electrical specification	
Operating Voltage	3.4~4.4 V, typical 3.8 V
Consumption (typical)	Undetermined
Interface	
LCD	4-lane MIPI_DSI, support horizontal screen, Resolution up to HD+ 1280×800@60fps
Camera	×3, 4-lane+2-lane+2-lane MIPI_C_SI, up to 21MP
TP	Capacitive touch screen
Audio	Lineout Interface、 receiver、 earphone and 3 sets of microphones
USB	×1, USB 2.0, Supports OTG
(U)SIM	×2
UART	×2
SD Card	×1
ADC	×2
I2C	×7
SPI	×4
PWRKEY	Internal pull up to VBAT
GPIO	18 GPIO reserved
ANT	Main antenna, Diversity antenna, GNSS antenna, WIFI/BT antenna